

SECTION VI

OPTIONS

Options are available for Series 2230/2240 Controllers which increase the functional use of the basic controller. Table 6-1 (page 6-2) lists all available options.

Options can be added to the basic controller at any time. Each option consists of all required components, mounting hardware, and instruction sheet.

TABLE 6-1. ALLOWABLE OPTION COMBINATIONS

OPTION TYPE	OPTION NUMBER	OPTION CODE ^a	OPTION
Enclosure Options - Choice of any or all within this group. May be combined with options from any other groups.	1170A	XK	Fan Assembly (5 HP Units Only) (Required When Enclosed Model 2242 Is Operated At 5 HP Rating)
Options Used To Convert Open Chassis Units Into Enclosed Package Controllers - Choice of one within this group. May be combined with options from any other groups.	1613	XK	Spacer Kit For Model 2232 Enclosed Controllers
	1638	XK	Hinge, Enclosure Cover
	1639	XK	Cover Assembly, Blank Type P0
	1639C	XK	Cover Assembly, Type P1
Power Options	1001	XK	Armature Contactor With Dynamic Braking (May Be Combined With All Options In This Group)
	1010	XK	Circuit Breaker - Two Pole (Model 2242 Only)
Input Signal Options - Choice of one within this group.	1036	XK, P	Four-Quadrant Acceleration/Deceleration
	1048	XK	Limit Switch Reversing
	1052	XK	Isolated Input
	1055	XK	Tachometer Follower, AC Or DC
Feedback Options - Choice of one within this group.	1190	XK	Torque Taper
	1670	XK	Pulse Tachometer Feedback/Follower
External Options - Choice of any or all within this group	1120	K	Operator Control Station - Remote
	1120A	K	Motor Speed Potentiometer, Ten-Turn With Analog Dial
	1120B	K	Motor Speed Potentiometer, One-Turn
	1120C	K	Motor Speed Potentiometer, Ten-Turn With Digital Dial
	1166	K	Extra Equipment Manuals
	1611	K	Card Guide
	1613	K	Spacer Kit (Model 2232 Only)
	1614	XK	Spacer Kit For Mounting Options On Models 2235 & 2236 Bracket

- a. XK = Factory Installed Or Field Kit
- K = Field Kit
- P = Plug-In Option